


picture will be changed after receiving of original

Description:

BSP to NPT adapter for usage in Flexalen PB systems.

Technical details:

Material:	ST37-2 - electro galvanized and yellow passivized
Dimensions:	O.D. 16 mm (½ ") – O.D. 75 mm (2 ½ ")
Nominal pressure:	PN16 (150 psi) @ 20°C
Thread:	ANSI/ASME B1.20.1, BSP
Assembly:	Adapter to be mounted on a BSP (male) threaded fitting as transition to NPT male thread with use of Teflon tape (not supplied)



	male thread	female thread	HEX [mm]	A [mm]	B1 [mm]	B2 [mm]	weight kg
Product code							
BSP-NPT1/2	1/2 NPT	1/2 BSP	27	28,00	19,05	14,22	*
BSP-NPT3/4	3/4 NPT	3/4 BSP	32	41,00	19,00	*	*
BSP-NPT1	1 NPT	1 BSP	41	35,00	23,88	14,22	*
BSP-NPT5/4	1 1/4 NPT	1 1/4 BSP	50	58,00	24,60	*	*
BSP-NPT6/4	1 1/2 NPT	1 1/2 BSP	55	64,30	25,40	*	*
BSP-NPT2	2 NPT	2 BSP	70	59,00	26,00	*	*
BSP-NPT2 1/2	2 1/2 NPT	2 1/2 BSP	88	74,50	38,50	*	*

* measurements will be announced after production