

# ThermaTape ThermaSmart<sup>®</sup> PRO SA

Accessories by Thermaflex<sup>®</sup>

Ultra-flexible tape made of direct extruded, closed-cell polyolefin foam with a colorless modified acrylate adhesives layer covered with a brown paper release liner



## Technical Properties

Properties	Units SI	Values	Testing method
<b>Physical properties</b>			
Thickness	mm	2 (+/-10%)	-
Foam density	kg/m <sup>3</sup>	18 - 40	-
Foam structure	-	Fine, closed-cells	-
Foam color	-	Anthracite	-
<b>Thermal properties</b>			
Application temperature range	°C	+5 to +40 (>15 for guaranteed optimal adhesion)	-
Maximum service temperature	°C	+95	-
Minimum service temperature	°C	-20	-
<b>Other</b>			
Shelf-life	month	12*	-

\*At 20 °C and 50 % relative humidity

## Availability

- Standard product dimension 50mm x 15m x 2mm

Product Code	Sales unit	Packaging unit
3702-050015-100	1/10**	1/10**

\*\*depending on country

### Disclaimer

All recommendations and information provided on this data sheet are based on our knowledge and experience. Product specifications are intended as guidelines. Since conditions of service are beyond our control, users must satisfy themselves that products are suitable for the intended use. No guarantee or warranty is given or implied or that any use of products will not infringe rights belonging to other parties. We reserve the right to change product design and properties without notification.