



Safety Data Sheet

Ultra M

Vers. 1/15

1 Identification of

1.1 Product

Ultra M

1.2 Company

Production plant NL
Thermaflex Isolatie bv
Industrieterrein Haven
Veerweg 1
P.O. Box 531
5140 AM Waalwijk
The Netherlands
tel. +31 - 416 567777
fax. +31 - 416 567788
Safety responsible: Marcel Houben

1.3 Emergency phone number Do call ThermoFlex Isolatie bv
+31 - 416 567710
Marjolein Mast-van de Polder



- 2 Product description** Ultra M is a cross-linked Thermoplastic Polyolefin Elastomeric foam containing flame-retardant additives and is produced in a extrusion process. Ultra M is based on XPE polymers and chemically foamed with an organic foaming agent. The foaming agent is known as non depleting substance to the ozone layer.
- 3 Hazards identification** XPE foam will burn when provided with an adequate amount of heat and oxygen; therefore do not expose the material to any flame or other source of ignition or heat. AC-formulations will not prevent the foam from burning, but will show improved fire retardant properties in terms of reduction of fire ignition and fire spread in well defined burn tests. Avoid direct contact with body skin, because AC-additives may in certain cases cause skin irritation in sensitive persons; we recommend to the wearing of gloves. Subject to reasonable care and cleanliness there are no obvious problems associated with the handling of XPE foams.
- 4 First aid measures** After contact to skin or eyes: No special measures. See 11 Toxicological information
- In case of fire: if smoke gases are inhaled, which contain mainly carbon dioxide (CO₂) and carbon monoxide (CO): Fresh air, coffee and possibly artificial respiration (call immediately a doctor) are the recommended measures.
If headache, nausea or vomiting occur, contact a doctor.
- If body skin is burned through contact with molten foam: Cool burned parts with water, but do not remove the foam from the skin. If skin burn grad 2 or 3 is reached: call immediately a doctor.
- 5 Fire fighting measures** Fire extinguishing mediums are: Water spray, extinguishing foam, CO₂-extinguisher. Use respirator/oxygen masks in enclosed areas. Avoid dense smoke and do not inhale the smoke gases from combustion.



Use safety glasses and protect skin/body with protective clothing against molten Ultra M.

6 Accidental release measures Not applicable

7 Handling and storage

7.1 Handling Practice reasonable care as a normal safety precaution. Fabrication areas should be well ventilated to carry away fumes, vapors and dust. Operatives should be assured of a supply of fresh air. The working environment should be kept clean and free of dust.

7.2 Storage Practice reasonable care and cleanliness; provide adequate distance between stacks as a safety precaution. Do not expose to any source of flame, ignition or heat. Recommended storage is inside due to UV light and heat sensitivity.

**8 Exposure controls/
personal protection**

Breathing protection:
Use special personal breathing respirator/mask or filter, in special fabrication areas (see 7.1 Handling) that are not well ventilated, in order to protect from fumes, vapors and dust.

Hand protection:
Wear gloves (cotton, wool or leather), when working in fabrication areas utilizing heat processes, to prevent from possible thermal injury from hot foam.

Eye protection:
Use goggles or face masks, when working in fabrication areas utilizing heat processes, to prevent possible contact with hot foam and thermal injury.

Body protection:
Wear clothes and shoes, to protect the full body skin, especially when working in fabrication areas utilizing heat processes, to prevent possible thermal injury (burns).



9	Physical and chemical properties	<p>Appearance: semi rigid closed cell, polyolefin plastic foam web, available in a wide variety of types.</p> <p>Odor: odorless</p> <p>Softening range: >70 °C</p> <p>Auto flammability: >300 °C</p> <p>Thermal decomposition: >160 °C</p> <p>Explosive properties: none</p> <p>Apparent density: 30-35 kg/m³</p> <p>Solubility in: water: insoluble organic solv.: insoluble, partly soluble, swelling; depending on solvent type.</p>
10	Stability and reactivity	<p>Avoid any temperature >160 °C over a period >10 min. Avoid any contact with strong oxidizing chemicals.</p> <p>Dangerous decomposition products: decomposition gases/vapors in heat fabrication processes combustion gases in case of fire.</p>
11	Toxicological information	<p>Toxicologically harmless. Polyolefin foams are among the most inert polymer foams and constitute no hazards in terms of normal handling and skin contact.</p>
12	Ecological information	<p>Environmentally harmless:</p> <ul style="list-style-type: none"> - insoluble in water: no contamination - insoluble in most solvents - degradable only by UV light (but: stabilizers added!) <p>Ultra M is produced (H)CFC free.</p>
13	Recycling & Disposal Considerations	<p>Recycling: Ask our sales responsible' s about product specific recycling possibilities.</p> <p>Disposal: When disposing of any wastes, observe all applicable national and local regulations.</p>
14	Transport information	<p>No restriction and non dangerous material in relation to transportation regulations according to regulations ADR/RID, IMO and IATA</p>
15	Other information	<p>For additional product information contact ThermoFlex Isolatie BV.</p>