

No. 13/1/B/2021

- | | | |
|----|--|---|
| 1. | Unique identification code of the product-type: | Ultra M - tubes PEF-EN 14313-ST(+) 85 – WS 01 |
| 2. | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Thermal insulation for building equipment and industrial installations |
| 3. | Manufacturer: | Thermaflex Izolacji Sp. z o.o., 58 – 130 Żarów, Poland
E-mail: biuro@thermaflex.com
Tel: +48748589666 |
| 4. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 3 |
| 5. | Harmonized standard: | PN-EN 14313+A1:2013-07 |
| 6. | Notified body or bodies: | 1454 Łukasiewicz Research Network - Institute of Mechanised Construction & Rock Mining, Branch in Katowice |
| 7. | Declared performance: | |

Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire Euroclass Characteristics	Reaction to fire: E_L	
Acoustic absorption index	Structure-borne sound transmission: NPD Sound absorption: NPD	
Thermal resistance	Thermal conductivity (λ): Average Temperature [°C] 40 λ [W/mK] 0,040	
Water permeability	Water absorption: WS 01	
Water vapour permeability	Water vapour diffusion resistance: NPD	
Compressive strength	Compressive strength is not applicable for products made of polyethylene foam	
Rate of release of corrosive substances	Trace quantities of water soluble ions and pH-value: NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances: NPD	PN-EN 14313+A1:2013-07
Continuous glowing combustion	Continuous glowing combustion: NPD	
Durability of reaction to fire against ageing/ degradation	Durability characteristics	
Durability of thermal resistance to fire against ageing/ degradation	Thermal conductivity Dimensions and tolerances Dimensional stability Durability characteristics Maximum service temperature: ST(+) 85 Minimum service temperature	They do not change with time - proven according to the point 4.2.5 PN-EN 14313+A1:2013-07
Durability of reaction to fire against high temperature	Durability characteristics	
Durability of thermal resistance to fire against high temperature	Durability characteristics Maximum service temperature – dimensional stability: ST(+) 85	

- | | | |
|----|-------------|--|
| 8. | Declaration | The performance of the product specified above is in accordance with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 and is the sole responsibility of the above mentioned manufacturer. |
|----|-------------|--|

Signed on behalf of the manufacturer:

Żarów, 20.05.2021



Janusz Tichoniuk, Managing Director



Wojciech Dźwigaj, Business Controller